

Tuburi flexibile de protectie Murrplastik - Ghid de alegere

	Seria	Material	Dimensiuni, metric	Temperaturi, grd Celsius	Clasa de foc, UL 94	Rez la strivire, N	Rez la oboseala, cicluri	Rezistenta la UV	Fara halogeni	Conform CE	Conform RoHS	Aprobari speciale
sectionate longitudinal	EW-LS	PE	M12...M25	-20...70	HB		4,000		•	•	•	
	EWX-LS	PE	M25...M50	-20...70	HB				•	•	•	
	EW-PA-LS	PA6	M06...M25	-40...120	HB		24,000		•	•	•	
	EWX-PA-LS	PA6	M25...M50	-40...120	HB		13,000		•	•	•	
	EWX-PP-LS	PP	M25...M32	-40...130	V2		2,000,000	•	•	•	•	
	EWX-PAE-LS	PA12	M20...M70	-40...120	HB		5,000,000	•	•	•	•	
	EWX-HY-LS	TPE	M25...M70	-45...160	HB		100,000	•	•	•	•	
duble	EWT-PA	PA6	M10...M70	-40...120	HB	900	15,000		•	•	•	
	EWT-PP	PP	M10...M70	-40...130	V2	700		•	•	•	•	
	EWT-PAT	PA6	M12...M50	-40...120	V2	1000			•	•	•	
standard	EW	PE	M10...M95	-20...70	HB	200	4,000		•	•	•	
	EWX	PE	M25...M50	-20...70	HB	600			•	•	•	
	EWS	PE	M20...M50	-20...70	HB	400	40,000		•	•	•	
	EWS/F	PE	M20...M50	-20...90	V2	100			•	•	•	
	EW-PP	PP	M10...M95	-40...130	V2	900	3,100,000	•	•	•	•	
	EWL-PP	PP	M06...M50	-40...130	V2	700	300,000		•	•	•	
	EWX-PP	PP	M25...M95	-40...130	V2	1500	2,000,000	•	•	•	•	
	EW-PA	PA6	M4,5...M95	-40...120	HB	800	24,000		•	•	•	
	EWL-PA	PA6	M10...M50	-40...120	HB	600	16,000		•	•	•	
	EWX-PA	PA6	M25...M50	-40...120	HB	1600	13,000	•	•	•	•	
	EW-PAB	PA6	M06...M95	-40...120	V0	1100			•	•	•	
	EW-PA-UL	PA6	M06...M70	-40...120	V0	1700			•	•	•	
	EWX-PA-UL	PA6	M25...M50	-40...120	V0	2200			•	•	•	
	EW-PAE	PA12	M06...M95	-40...120	HB	500	5,000,000	•	•	•	•	
	EWX-PAE	PA12	M25...M95	-40...120	HB	1200	5,000,000	•	•	•	•	
	EW-HY	TPE	M12...M95	-45...160	HB	500	250,000	•	•	•	•	
	EWX-HY	TPE	M25...M95	-45...160	HB	900	1,000,000	•	•	•	•	
	EW-PRF	PA12	M10...M95	-40...105	V2	1100	16,000		•	•	•	
	EW-PAT	PA6	M06...M50	-40...120	V2	1400			•	•	•	
	EWL-PAT	PA6	M12...M50	-40...120	V2	1000			•	•	•	
EW-PRT	PA12	M06...M50	-40...120	V2	600	700,000	•	•	•	•		
speciale	EW-PA-EX	PA12	M16...M95	-40...110	HB	400	1,000,000		•	•	•	
	EF	TPE	50 x 34 mm	-45...160	HB	1000			•	•	•	
	EWB	HDPE	M25...M25	-15...90	HB	650			•	•	•	
	EW-TEF	PTFE	M4,5...M25	-200...260	V0	250			•	•	•	
	EW-PAP	PA6 M	M12...M50	-40...120	HB	1200	24,000		•	•	•	
	EW-PATM	PA6 M	M25...M40	-40...120	V2	1300		•	•	•	•	
	EL	PVC	M25...M50	-15...60	V2	500			•	•	•	
	ELS	PVC	M06...M50	-25...80	V2	1200			•	•	•	
	GF	PA6.6	3...78 mm	-50...150	V2				•	•	•	
	GF-P	Poliester	3...87 mm	-55...150	V2				•	•	•	

Cablul.ro - Solutii in jurul cablurilor