

## Fastening clip type BFC



### Product information

The fastening clip BFC 5.5 flange is made of flame-retardant polyamide 6. It is used to fix the cable entry plates type KDP/Z. The clip is smashed using a hammer.

Special benefits of the BFC room integrity system are:

Easy assembly from one side  
 Suitable for standard drilling 5.5 mm

### Information, conformities and approvals



Article	Order No.	Color	PU pcs.
BFC 5.5	87621440	Black	200

## KDL/E cable entry system

Article	Order No.
BFC 5.5	87621440

## Material properties





## Fastening clip type BFC

### Fire properties



Fire classification V0

### Technical information



Halogen-free



LABS free



According to EN -2-1

### Conformity



RoHS (EC Directive 2011/65/EU)

### General information



Made in Germany

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.