


# **Typ SVG**





### PRODUCT INFORMATION

The SVG conduit couplings are made of specially modified polyamide 6. The material is halogen, phosphor and cadmium-free. The conduit couplings are used as an extension or for the repair of cable protection conduits and feature the following advantages:

- Easy assembly by latching
- · Split version makes routing of cables easy
- Can also be screwed on

## **SPECIFICATIONS**



mod. polyamide PA 6



-40 - 110 °C short term 140 °C



IP 42 IP 54 bolted



acc. to UL94 V0 self-extinguishing





Туре	Order No.	Colour	Suitable for Murrflex	A mm	B mm	C mm	G mm	Pack qty.
Conduit connector suitable for Murrflex EW and EWX								
SVG 21	83701630	Black	M25/P21(S)	31.00	36.00	50.00	5.50	25
SVG 29	83701632	Black	M32/P29(S)	36.80	44.00	54.00	5.50	25
SVG 36	83701634	Black	M40/P36(S)	44.80	50.00	66.00	5.50	10
SVG 48	83701636	Black	M50/P48(S)	56.80	64.00	66.00	5.50	10
SVG 21	83701610	Grey	M25/P21(S)	31.00	36.00	50.00	5.50	25
SVG 29	83701612	Grey	M32/P29(S)	36.80	44.00	54.00	5.50	25
SVG 36	83701614	Grey	M40/P36(S)	44.80	50.00	66.00	5.50	10
SVG 48	83701616	Grey	M50/P48(S)	56.80	64.00	66.00	5.50	10

### **MATERIAL PROPERTIES**



mod. polyamide PA 6

## **THERMAL PROPERTIES**



Temperature / temperature range

-40 - 110 °C short term 140 °C

## **MECHANICAL PROPERTIES**



**Protection class** 

IP 42

IP 54 bolted



# **Typ SVG**

#### **FIRE PROPERTIES**



Fire classification

acc. to UL94 V0 self-extinguishing

#### **TECHNICAL INFORMATION**



Halogen-free

#### **CONFORMITY**



RoHS (EC Directive 2011/65/EU)

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.