# Type DS (seal)



## PRODUCT INFORMATION

The DS seal is made of specially modified NBR. The material is halogen, phosphor and cadmium-free.

The DS seal can be used for the SA-Jumbo flange connection and for the KFW-Jumbo 90° flange connection to achieve a tightness of IP 65.

## **SPECIFICATIONS**



Туре	Order No.	Colour	<b>Pack</b> qty.
Seal for IP 65 (conduit connection/fitting):			
DS 70	83101238	Black	1
DS 95	83101240	Black	1

#### **MATERIAL PROPERTIES**



## **THERMAL PROPERTIES**

**Temperature / temperature range** -40 – 110 °C transient / short term 140 °C

## **FIRE BEHAVIOUR**



**Fire classification** i.a.w. UL94 V0 self-extinguishing

## **TECHNICAL INFORMATION**



Halogen-free

#### CONFORMITY



RoHS (EC Directive 2011/65/EC)



## Type DS (seal)

de in Made in Germany

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.