


Type GF-P (braided conduit)



Cable protection conduit closed

PRODUCT INFORMATION




The GF-P braided conduits are made of specially modified polyester. With this material and the special braiding, the conduit is extremely durable and elastic in both the radial and axial directions. It can be used to bundle and protect a large number of cables and individual wires of all types. The elastic braiding means that configuration of the conduit can be very variable.




Additional advantages of the GF-P braided conduit include:

- Very good mechanical and thermal resistance
- Good chemical resistance
- Very low levels of smoke gas
- Very high abrasion resistance

Specification:
EN 45545-2 3x HL3

SPECIFICATIONS


-  mod. polyester
-  -55 – 150 °C short term 175 °C
-  acc. to UL94 V2 self-extinguishing


Type	Order No.	Colour	Nominal widths NW	Size range mm	Surface covering in %	Weight kg/100m	MOQ m
GF-P 3	83342008	Black	4.00	2.00 / 6.00	93.00	0.41	500
GF-P 4	83342010	Black	4.00	3.00 / 7.00	93.00	0.58	200
GF-P 6	83342012	Black	6.00	5.00 / 9.00	86.00	0.70	200
GF-P 8	83342014	Black	8.00	7.00 / 12.00	87.00	0.74	200
GF-P 10	83342016	Black	10.00	8.00 / 15.00	77.00	0.91	200
GF-P 12	83342018	Black	12.00	8.00 / 15.00	74.00	0.94	200
GF-P 16	83342020	Black	16.00	12.00 / 24.00	80.00	1.50	100
GF-P 20	83342022	Black	20.00	16.00 / 32.00	75.00	1.75	100
GF-P 22	83342024	Black	22.00	18.00 / 33.00	84.00	1.90	100
GF-P 30	83342026	Black	30.00	28.00 / 37.00	78.00	2.65	100
GF-P 40	83342028	Black	40.00	32.00 / 45.00	77.00	3.18	50
GF-P 50	83342030	Black	50.00	30.00 / 55.00	79.00	3.88	50
GF-P 70	83342032	Black	70.00	60.00 / 88.00	87.00	5.94	50
GF-P 4	83342050	Grey	4.00	3.00 / 7.00	93.00	0.58	200
GF-P 6	83342052	Grey	6.00	5.00 / 9.00	86.00	0.70	200
GF-P 8	83342054	Grey	8.00	7.00 / 16.00	87.00	0.74	200
GF-P 10	83342056	Grey	10.00	8.00 / 15.00	77.00	0.91	200
GF-P 12	83342058	Grey	12.00	8.00 / 15.00	74.00	0.94	200
GF-P 16	83342060	Grey	16.00	12.00 / 24.00	80.00	1.50	100
GF-P 20	83342062	Grey	20.00	16.00 / 32.00	75.00	1.75	100
GF-P 22	83342064	Grey	22.00	18.00 / 33.00	84.00	1.90	100
GF-P 30	83342066	Grey	30.00	28.00 / 37.00	78.00	2.65	100
GF-P 40	83342068	Grey	40.00	32.00 / 45.00	77.00	3.18	50
GF-P 50	83342070	Grey	50.00	30.00 / 55.00	79.00	3.88	50
GF-P 70	83342072	Grey	70.00	60.00 / 88.00	87.00	5.94	50

Type GF-P (braided conduit)

MATERIAL PROPERTIES

 mod. polyester

THERMAL PROPERTIES

 **Temperature / temperature range**
-55 – 150 °C short term 175 °C

FIRE PROPERTIES

 **Fire classification**
acc. to UL94 V2 self-extinguishing

Smoke emission class
SR2 DIN 5510-2

Flammability classification
S4 DIN 5510-2

Fire properties as per EN 45545-2
C.I.T. R22 / R23 HL3 = 0.1
LOI R22 / R23 HL3 = 34.4
Ds (max.) R22 / R23 HL3 = 142

TECHNICAL INFORMATION

 **Halogen-free**
DIN 53474

CONFORMITY

 **RoHS (EC Directive 2011/65/EU)**

APPROVALS AND OPERATING PERMITS

 **EU railway approval**
EN 45545-2 R22/R23 3x HL3

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.

© Murrplastik Systemtechnik GmbH • proID_64655~20210303~890283~suv_gf_p